



The **MUTOH ValueJet 2638X 104**" Eco-Solvent CMYKx2/CMYK LcLmLk printer, builds upon MUTOH's made in Japan reputation and delivers superior print quality and outstanding speeds at an affordable price. Enhance your printing capabilities with the award-winning MUTOH VerteLithTM RIP Software and a complimentary one-year subscription to SAi Flexi DESIGN MUTOH Edition—a combined value of \$1,600. VerteLith RIP optimizes all of the capabilities the VJ-2638X has to offer and produces the best-possible gradients, skin tones and vivid colors.

This super-wide printer produces billboards, banners, vehicle wraps and signage with ease using technologies such as Variable Dot, i² Intelligent Interweave and DropMaster. The VJ-2638X is paired with MUTOH's GREENGUARD Gold certified MS31Eco-Solvent ink, suitable for use in sensitive environments like hospitals, child care facilities and more, all while providing users a larger color gamut, outstanding durability, and improved dot gain.



BILLBOARDS



BANNERS



WRAPS



SIGNAGE

MUTTOH ValueJet 2638X

NEW VERTELITH RIP SOFTWARE

MULTI-STAGE HEATER SYSTEM

USER FRIENDLY CONTROL PANEL

i² INTELLIGENT **INTERWEAVE**

DROPMASTER INK **PLACEMENT TECHNOLOGY**

www.MUTOH.com | 1-800-99MUTOH



POWERED BY VERTELITH™ RIP SOFTWARE





MUTOH's Genuine VerteLith™ RIP software • MUTOH CMYK wide color gamut ICC profile. bundled with complimentary one-year subscription to SAi Flexi DESIGN MUTOH Edition optimizes the VJ-2638X by:

- · Auto-population of named Pantone coated/uncoated spot colors.
- · Soft proof simulates the color of the printed image on screen before printing.
- · MUTOH Clear Tone half tone technology.

- · Automated layout processing and printing.
- · "What-you-see-is-what-you-get" RIP preview.
- · Tab customization.
- · Color management function.
- Printing log function.

VJ-2638X printer features include:

· Staggered dual print heads.

- i² Intelligent Interweave technology reduces
- DropMaster ink dot placement technology.
- · MUTOH Status Monitor (MSM) checks printer status in real time.
- Multi-stage heater system for faster drying
- · Heavy Duty 220lb motorized feed and takeup unit.

VALUEJET 2638X SPECIFICATIONS

Printing systems	Drop-on-demand Micro Piezo Inkjet Technology
Print head height	Three level adjustment: Low 1.5mm, Mid. 2.5mm, High 4.0mm
Print heads	2
Max print resolution	1440x1440dpi
Print modes	1440/1080/720/540/360dpi 29 modes
Media width	104 inches
Media capacity	ø 5.9" dia / 2" & 3" cores /Roll media 220lbs or less
Max media thickness	Low 0.3mm, Mid. 1.3mm, High 2.8mm
Max printable width	104 inches
Height adjustment	Manual
RIP software	MUTOH VerteLith™

	Ink	Туре	MS31 Ink Eco-Solvent
		Ink Set	CMYKx2, CYMK LcLmLk
		Volume	220ml/440ml cartridges/ 1L bags with optional adapters
		No. of slots	8

Interface	Gigabit-Ethernet (1000BASE-T)
Power Requirements	AC 110-120V± 10%, 50/60Hz ± 1Hz
Printable Environment	Temperature: 68-89.6°F Humidity: 40-60%RH (non condensing) Rec. environment: Temperature: 71.6-86°F
Power Consumption	Main: Operation status 77W or less Standby: 52W or less
Dimensions (WxDxH)	Printer including stand: 146"x34.9"x49.65" cover closed
Weight	Body: 534lbs Stand: 91lbs