

54" DYE-SUBLIMATION PRINTER
XpertJet 1341WR Pro



MUTOH



APPAREL



HOME DECOR



SOFT SIGNAGE



FLAGS

BUILT FOR PROFESSIONALS

- ADJUSTABLE PINCH ROLLERS
- 3-STEP CARRIAGE HEIGHT
- MAINTENANCE ACCESS DOOR
- COMPACT FOOTPRINT
- DH21 DYE-SUB INK





The **XpertJet 1341WR-Pro** is a high-speed 54" dye-sublimation inkjet printer built on a refined platform that inherits the proven performance of the XpertJet series. The XPJ-1341WR-Pro features a MUTOH AccuFine print head with best-in-class dot placement accuracy and i-screen intelligent interweaving technology, delivering smooth, banding-free output at production speeds up to 314 ft²/hr.

MUTOH DH21 dye-sublimation transfer ink provides optimum media transfer, achieving high-density colors with less ink consumption. Fast ink-drying times enable printing on thinner and lighter transfer papers. Excellent jetting and color stability support prolonged print runs. DH21 ink is available in a CMYK configuration in 1L high-capacity ink bags.

The XPJ-1341WR-Pro delivers high-quality graphics onto a wide range of materials such as apparel, sports uniforms, flags, banners, soft signage, custom home décor, and more.

- **MUTOH AccuFine printhead.**
- **Latest i-screen interweave patterns.**
- **AccuFine printhead.**
- **i-screen print effect technology.**
- **Drop Master 2.**
- **Feed Master.**
- **Media Tracker.**
- **Nozzle Area Select.**
- **DH21 dye-sublimation ink.**
- **44lb take-up unit (optional).**

SPECIFICATIONS

PRINTHEAD

Printing Method	Drop-on-demand Micro Piezo Inkjet Technology
Printhead Height	Low: 1.5mm Mid: 2mm High: 2.5mm
Printheads	1
Roll Media Width	Max: 53.97" Min: 19.68"
Max Roll Diameter	ø5.9"
Core Diameter	2" or 3" cores
Max Roll Weight	41.8lbs
Max Media Thickness	1.3mm
Max Printable Width	53.58"
Printer Resolution	1200 x 1200 dpi
Printer Weight	Body: 134.4lbs Stand: 44lbs
Dimensions (WxDxH)	75.4" x 26.9" x 47.9" (with cover closed)
RIP software	6-month trial to Wasatch SoftRIP

INK

Type	DH21 Dye-sublimation ink
Ink Set	4-Color (CMYK)
Volume	1L ink bag (adapters required)

AUXILIARY

Interface	Gigabit-Ethernet (1000BASE-T) Recommend CAT6+
Power Requirements	AC 100-120V± 10% (90V-132V) or 200-240V± 10% (180V-264V) Frequency: 50/60Hz ± 1Hz
Printable Environment	Temperature: 68-89°F Humidity: 40-60%RH (non condensing) Rec. environment: Temperature: 72-86°F
Power Consumption	Main: Operation status 190W or less Standby: 14W or less

Get started with a 6-month trial to Wasatch SoftRIP. The sophisticated RIP software made easy. With simple setup, intuitive workflow, and powerful print controls, SoftRIP saves you time and money while producing excellent quality color.

